®

Item #:

Project #:



Model JET514V shown

4 times faster than conventional ovens.

Heavy Volume | Combination Cooking This category of combination oven is ideal for...

Application:

- Wine bars
- Country club,Bakery/cafés
- Pubs - Kiosks
- Convenience stores
- Supermarkets

Through put potential:

- 6" Inch toasted sub sandwiches, 50 per hour
- 1 portion of 4 frozen crispy chicken wings, 25 portions (84 wings) per hour
- 1 frozen pre-baked fruit filled pastry, 20 per hour
- 12" frozen pizza, 10 per hour
- 1 frozen, pre-baked fruit filled pastry, 20 per hour

Location of oven(s):

- Kitchen shelf
- Kitchen countertop, single or stacked
- Equipment stand, single or stacked

All ACP, Inc. commercial ovens are backed by our Culinary Center. Call us with any question regarding food preparation, menu development and cooking times. 866-426-2621.



High Speed Combination Oven

Menumaster® Commercial Jetwave™ Model JET514V

Power Output

- Convection:
 - 2700 W
 - 65°-250°C (150°-475°F) temperature range
 - Convected air for enhanced toasting and browning
- Microwave:
 - 1400 W
 - Heats quickly, reduces cooking time

Cuts Costs

- No need for costly ventilation hood catalytic convertor filters grease and odors from the air. Integrated recirculating catalytic converter.
- Uses less energy than a conventional oven.
- Eliminates need for pre-cooking and holding.
- Uses quarter size metal trays, pans and screens.

Simplifies Cooking

- Touch pad operation for consistent results.
- Controls are intuitive and simple to use.
- Stores up to 100 menu items.
- Four stage cooking option.
- USB Port compatible with standard flash drives, updates programming in seconds.
- 34 liter (1.2 cubic ft.) oven capacity.
- Door opens 90°+ for full access to the oven cavity.
- Single rack position for optimal and consistent cooking results.

Easy to Use and Maintain

- Braille touch pads are ADA compliant.
- Stainless steel door and interior.
- Removable, cleanable air filter and clean filter reminder protect oven components.
- Backed by the ACP, Inc. 24/7 ComServ Support Center 866-426-2621.



front view 19-1/4" (489) 18-1/8" (460) 18-1/2" (444) 42-7/8" (1089)

Installation clearance: 7" for top of oven 2" for all other sides

Drawings available from KCL CADlog - techs@kclcad.com

Specifications		
Model	JET514V	UPC Code 728028244748
Cooking Power*	2700W	1400W
	Convection	Microwave
Configuration	Countertop	
Control System	Touch	
Programmable Control Pads	10	
Braille	Yes	
Total Programmable Settings	100	
Power Levels	11	
Max. Cooking Time	20:00	
Stackable	Yes	
Time Entry Option	Yes	
Microwave Distribution	Rotating antennas, top	
Magnetrons	2	
Display	LED-backlit LCD	
Stage Cooking	Yes, 4	
Door Opening	Grab & Go	
USB Port	Yes	
Temperature Range	70° - 250°C (150° - 475°F)	
Air Filter	Yes, removable, with clean filter reminder	
Rack	1 rack position, removable	
Exterior Dimensions	H 460 (18 1/8")	
Cavity Dimensions	H 267 (10 ½")	
Door Depth	994 (39 %"), 90°+ door open	
Usable Cavity Space	34 liter (1.2 cubic ft.)	
Exterior Finish	Powder coat painted	
Interior Finish	Stainless steel	
Power Consumption	2900 W, 13 A	
Power Output*	1400 W* Microwave	
Power Source		6 A single phase
Plug Configuration / Cord	CEE 7/7 "Schuko"	1.5 m (5 ft.)
Frequency	2450 MHz	·
Product Weight	50 kg. (110 lbs.)	
Ship weight (approx.)	52 kg. (115 lbs.)	
Shipping Carton Size	H 546 (21 ½")	W 540 (21 ¼") D 756 (29 ¾")

Specifications

Oven shall combine two cooking modes: convection and microwave for high speed cooking. Control panel shall be programmable with the ability to program up to 100 menu items, single or double digit entry. Programs shall be automatically updated using a USB Port that is compatible with standard USB flash drives. There shall be 11 power levels and 4 cooking stages. Microwave output shall be 1400 watts and distributed from the top of the cavity. The 2700 watt convection oven shall provide a temperature range from 70° - 250° C (150° - 475° F) in 5° increments . The convection fan located in the back of the cavity shall distribute the heat throughout the cavity to further enhance browning. Maximum microwave cooking time shall be 20 minutes. Oven shall have a powder coat exterior. 34 liter (1.2 cubic ft.) oven cavity shall be stainless steel construction with stainless oven door. Interior shall have 1 rack position. Air filter shall be easily accessible and removable from the front of the oven and have a "clean filter" reminder feature. Oven shall be stackable. Microwave oven shall comply with standards set by the U.S Department of Health and Human Services and ETL listed for safety and sanitation.

Optional Accessories

- Pizza stone
- Drip tray
- Oven paddle

Warranty

Warranty Certificate for this product can be found on the ACP, Inc. website at:

www.acpsolutions.com/warranty

Service

All products are backed by the ACP, Inc. 24/7 ComServ Support Center.





Measurements are in millimeters
* IEC 60705 Tested ** Includes handle

Part No. 20154116 Updated 6/19/2015 Original Instructions



©2014 ACP, Inc. Cedar Rapids, Iowa 52404